



J01/ 604/ 1997 • RO 11358544
Capital social 318.075.900,24 RON integral versat



SC KRONOSPAN SEBEŞ SA
Str. Mihai Kogălniceanu Nr. 59 • Sebes • 515800 • Alba • România
Tel.: +40 258 801 100 • Fax: +40 258 801 199
office.sebes@kronospan.ro • www.kronospan.ro

Nr.9714/ 07.07.2015

RAPORT PRIVIND EMISIILE SC KRONOSPAN SEBES SA Trimestrul II - 2015

SECTIA CHIMICA

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Trimestrul II		
			Aprilie	Mai	Iunie
A1/ Instalatia de producere formaldehida	COT	50	2,7	3,1	3,2
	formaldehida	5		1,07	

*Valoarea medie lunara - monitorizare on-line

SECTIA PAL

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Trimestrul II		
			Aprilie	Mai	Iunie
P17/ uscare aschii in uscator Krono-plus	COV	150		42,1	
	formaldehida	20	2,54	2,65	1,91
	pulberi*	20		3,14	
	CO	250		196,7	
	NO _x	500		431,9	
P19/ exhaustare noxe presa din zona de evacuare	SO _x	500		0,00	
	COV	150		51,6	
	formaldehida	20		3,15	
P22/ desprafuire grup 1 mori	pulberi	50		1,02	
				2,30	
P23/ desprafuire grup 2 mori	pulberi	50		5,07	
P24/ desprafuire mori (zona seco)	pulberi	50		1,51	
P35/ exhaustare formatizat placi si circulare diagonale	pulberi	50		1,42	

* Monitorizare continua, valorile monitorizarii continue s-au situat in intervalul 0,3 mg/Nmc si 7,1 mg/Nmc
Nu s-au inregistrat depasiri a limitei admise.

Trimestrial se efectueaza o monitorizare discontinua, masura stabilita de GNM CJ Alba prin R.I. nr.14384/12.08.2011

SECTIA MDF

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Trimestrul II		
			Aprilie	Mai	Iunie
P5/ ciclon 1 - uscare fibra	COV	150		36,3	
	formaldehida	20		2,68	
	pulberi*	50		21,45	
	NO _x	500		166,7	
	SO _x	500		8,6	
P5/ ciclon 2 - uscare fibra	COV	150		36,1	
	formaldehida	20		3,19	
	pulberi*	50		22,34	
	NO _x	500		167,4	
	SO _x	500		5,7	
P5/ ciclon 3 - uscare fibra	COV	150		37,3	
	formaldehida	20		2,77	
	pulberi*	50		22,27	
	NO _x	500		168,8	
	SO _x	500		6,7	
P5/ ciclon 4 - uscare fibra	COV	150		39,6	
	formaldehida	20		2,60	
	pulberi*	50		16,97	
	NO _x	500		168,1	
	SO _x	500		7,6	
P6/ evacuare noxe alimentare si evacuare presa placi MDF	COV	150		11,7	
	formaldehida	20		3,44	
	pulberi	50		0,89	
P8/ pregatire aschii - tocarea fibre	pulberi	50		0,77	
P14/ slefuire; P15/ calibrare placi	pulberi	50		1,93; 3,24	
P16/ formatizare placi	pulberi	50		0,83	

*Trimestrial se efectueaza o monitorizare discontinua, masura stabilita de GNM CJ Alba prin R.I. nr.14384/12.08.2011.

** Monitorizare continua, valorile monitorizarii continue s-au situat in intervalul 3,7 mg/Nmc si 26,3 mg/Nmc

Nu s-au inregistrat depasiri a limitei admise

APA

Emisar/ categoria apei evacuata	Indicator	Limita admisa (mg/l)	Trimestrul II		
			Aprilie	Mai	Iunie
Ape uzate evacuate in reteaua de canalizare oraseneasca	temperatura	max 40°C		16	
	pH	6,5 – 8,5		6,85	
	suspensii	350		260	
	CBO5	300		<3,0	
	CCO-Cr	500		<30,0	
	NH ₄	30		0,553	
Ape tehnologice conventional curate evacuate in emisar	temperatura	35°C	15	22	
	pH	6,5 – 8,5	7,67	7,46	
	suspensii	60	25,0	17,3	
	CBO5	25	21,0	22,0	
	CCO-Cr	125	37,6	38,2	
	extractibile	20	<20 (1,6)	<20 (3,0)	
	reziduu fix	2000	398	221	
	NH ₄	3	2,20	2,65	

Ape uzate preepurare	pH	6,5 – 8,5	6,89
	suspensii	350	206
	CCO-Cr	500	<30,0
	extractibile	30	<20 (6,0)
	detergenti	25	0,142
	produse petroliere	5	4,23

Director Productie

Adrian BACILA



Intocmit: Luminita MARIN