



J01/604/1997 • RC 11358544  
Capital social 318.075.900,24 RON integral vărsat

**SC KRONOSPAN SEBEȘ SA**  
Str. Mihal Kogălniceanu Nr. 59 • Sebeș • 515800 • Alba • România  
Tel.: +40 258 801 100 • Fax: +40 258 801 189  
[office.sebes@kronospan.ro](mailto:office.sebes@kronospan.ro) • [www.kronospan.ro](http://www.kronospan.ro)

Nr. 15166/ 07.10.2015

## RAPORT PRIVIND EMISIILE SC KRONOSPAN SEBES SA Trimestrul III – 2015

### I. AER

#### SECTIA CHIMICA

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Trimestrul III		
			Iulie	August	Septembrie
A1/ Instalatia de productie formaldehida	COT*	50	1,7	1,9	3,2
	formaldehida	5	1,2		
A2/ Instalatia de productie rasini pulbere	formaldehida	20	2,2		
	pulberi	20	1,34		
A3/ Exhaustare generala hala rasini pulbere	formaldehida	20	0,78		
	pulberi	20	1,16		

\*Valoarea medie lunara - monitorizare on-line

#### SECTIA PAL

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Trimestrul III		
			Iulie	August	Septembrie
P17/ uscare aschii in uscator Krono-plus	COV	150	59,3		
	formaldehida	20	2,43	2,89	3,20
	pulberi*	20	4,21		
	CO	250	167,9		
	NO <sub>x</sub>	500	391,6		
	SO <sub>x</sub>	500	0,0		
P19/ exhaustare noxe presa din zona de evacuare	COV	150	55,9		
	formaldehida	20	3,50		
	pulberi	50	0,75		

\* Monitorizare continua, valorile monitorizarii continue s-au situat in intervalul 1,1 si 5,7 mg/ Nmc.

Trimestrial se realizeaza o monitorizare discontinua, masura stabilita de GNM CJ Alba prin R.I. nr.14384/12.08.2011.

Nu s-au inregistrat depasiri a limitei admise.

## SECTIA MDF

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Trimestrul III		
			Iulie	August	Septembrie
P5/ ciclon 1 - uscare fibra	COV	150	43,1		
	formaldehida	20	2,10		
	pulberi	50	19,93		
	NO <sub>x</sub>	500	133,3		
	SO <sub>x</sub>	500	2,9		
P5/ ciclon 2 - uscare fibra	COV	150	43,3		
	formaldehida	20	1,95		
	pulberi	50	23,66		
	NO <sub>x</sub>	500	133,9		
	SO <sub>x</sub>	500	1,9		
P5/ ciclon 3 - uscare fibra	COV	150	48,5		
	formaldehida	20	1,74		
	pulberi*	50	18,85		
	NO <sub>x</sub>	500	117,5		
	SO <sub>x</sub>	500	1,9		
P5/ ciclon 4 - uscare fibra	COV	150	45,9		
	formaldehida	20	1,79		
	pulberi	50	17,96		
	NO <sub>x</sub>	500	133,3		
	SO <sub>x</sub>	500	1,0		
P6/ evacuare noxe alimentare si evacuare presa placi MDF	COV	150	12,6		
	formaldehida	20	3,43		
	pulberi	50	1,03		

\*Monitorizare continua, valorile monitorizarii continue s-au situat in intervalul 2,6 si 25,4 mg/ Nmc.

Trimestrial se realizeaza o monitorizare discontinua, masura stabilita de GNM CJ Alba prin R.I. nr.14384/12.08.2011.

Nu s-au inregistrat depasiri a limitei admise

## II. APA

Emisar/ categoria apei evacuata	Indicator	Limita admisa (mg/l)	Trimestrul III		
			Iulie	August	Septembrie
Ape uzate evacuate in reseaua de canalizare oraseneasca	temperatura	max 40°C	18,0		
	pH	6,5 – 8,5	6,75		
	suspensii	350	81,8		
	CBO5	300	20,0		
	CCO-Cr	500	<30,0		
	NH <sub>4</sub>	30	5,29		
Ape tehnologice conventional curate evacuate in emisar	temperatura	35°C	23,4		
	pH	6,5 – 8,5	6,71		
	suspensii	60	7,75		
	CBO5	25	20,0		
	CCO-Cr	125	56,4		
	extractibile	20	<20 (2,10)		
	reziduu fix	2000	188		
NH <sub>4</sub>	3	2,01			
Ape uzate preepurate	pH	6,5 – 8,5	8,15		
	suspensii	350	129		
	CCO-Cr	500	<30,0		
	extractibile	30	<20 (3,70)		
	detergenti	25	0,423		
	produse petroliere	5	4,611		

Director Productie

Adrian BACILA

Intocmit: Luminita MARIN

